Mezalok Connector Answers Need for Fast, Rugged, Highly-Reliable Solution for Extreme Environments

At VITA Standards Organization meetings, customers consistently voiced a need for an improved stacking connector to be used as an alternative to the VITA 42 connector. They wanted a connector to be as least disruptive as possible, but specifically address Mil Aero requirements in regard to thermal cycling durability, mating cycle durability, mechanical robustness and second generation protocols. A number of customers sponsored the VITA 61 working group and Tyco Electronics (TE) embarked on development of the Mezalok. **Background**
The original VITA 42 XMC connectors were not designed to specifically address military applications as a central design goal. The demanding environment of military applications presents several design challenges due to the high levels of vibration and thermal cycling that can stress a connector's performance and decrease signal integrity. Cracked solder joints from thermal cycling and damaged contacts from stubbing during mating also need to be considered.

As a result of these issues and other feedback from customers, TE engineering began a development program to design a new high-reliability XMC connector to meet the demanding requirements of military needs. Goals for the development program included:
• Uniform solderball and contact retention features of mated connectors to improve reliability
• High-reliability socket contact design based on MIL-C-55302 Mini-Box contact
• Improved thermal cycling stability—2000 or more thermal shock cycles
• Anti-stub design with protected lead-in
• Improved durability of 500 cycles minimum
• Footprint compatibility with existing XMC board layouts
Mezzanine Boards Provide Flexibility
Mezzanine boards give additional flexibility for systems by providing for expanded functionality and modularity to a pc board. They allow existing boards to be re-configured, upgraded, or customized by the addition of the mezzanine card. Typical applications include application-specific high-speed input/output (I/O) protocols, graphics, memory, and digital-signal processing. Mezzanine boards are widely used in the telecommunications, industrial, and military/aerospace markets.

Solderball: Compliancy Brings Reliability
The Mezalok header and receptacle connectors attach to the boards by well-established ball grid array technology. The solder tail design of Mezalok connectors uses a proven compliant design to provide robust, uniform solder joints. The compliancy is important for two reasons.

First, it accommodates variations in the board-to-connector coplanarity. Ideally, the solder balls would meet the pc board pads along a perfect plane. In reality, small

variations exist. With a noncompliant contact design, lack of coplanarity can result in non-uniform solder joints—some stronger or weaker than others. Compliancy helps ensure uniform reliable joints.

Second, compliancy is much more forgiving of thermal cycling, which can lead to cracking of solder joints if some flexibility is not achieved. Since different parts of the connection—pc board, solder joint, and connector housing and contacts—have different coefficients of thermal expansion, a rigid design can lead to failure of the joint. In a military environment, with higher levels of vibration, even small cracks can quickly lead to joint failure.

High-Reliability Contacts for Demanding Environments
The contact design selected for the Mezalok connector was based on the MIL-C-55302 Mini-Box contact. This contact has years of proven performance in military environments. The design used four spring members to provide contact on all four sides of the pin, a configuration that works well in high-vibration applications. The redundant four points of contact ensure a low-resistance, reliable connection under trying application circumstances.

The shape of the Mini-Box springs, with their gentle radii, also allows lower insertion forces while maintaining high normal forces when mated. The lower insertion force, in turn, means easier engagements and disengagement of connectors, higher durability, and less chance of damage.

Improved Thermal Stability
As mentioned, thermal cycling can be a major failure mechanism in connectors used in military applications. The compliant design of the solder balls accommodates thermal expansion and contraction. In addition, housings are made of liquid crystal polymer (LCP), which has a low coefficient of thermal expansion and withstands soldering temperatures, including the higher temperatures associated with lead-free solders. Overall, the new design presents a thermally stable connector that withstands thermal extremes well. The connector has been tested to 2000 thermal shock cycles with no failures.

Anti-Stub Design
Stubbing occurs when the pin contact does not mate properly with the receptacle. In severe stubbing, the pin can even miss the socket entirely, being pushed into the housing on the outside of the socket. Stubbing can result in damaged contacts, high resistance, and lower cycle life. The design of the Mezalok connector eliminates stubbing through four main features First, the Mini-Box contact is boxed at the end so that there are no exposed spring ends to become deformed or present a stubbing surface.

Second, the receptacle housing provides generous chamfered lead-ins to the Mini-Box contacts. The ends of the contacts are protected by the housing overhanging and protecting the ends of the receptacle.

Third, the pin connector is fully shrouded to reduce the possibility of pins being bent.

Fourth, the tip of the pin is tapered to help direct entry into the receptacle.

Improved Durability
The durability target for connectors used in military and aerospace applications is 500 mating cycles. Existing VITA 42 XMC connectors are only specified for 100 mating cycles. The new design meets military durability requirements. Redundant four-sided configuration of the Mini-Box contacts means less wear and tear on the contacts since each spring can have a lower individual normal force.

Mezalok contacts are a high-performance copper alloy selectively plated with 50 micro-inches of gold in the mating areas (with 30 micro-inches as an option). Gold plating, of course, ensures a low-resistance mating without corrosion or films developing over time.

XMC Compatibility
Mezalok connectors use the same pc board footprint as VITA 42 connectors. While the two connectors are not intermateable, the Mezalok connector is a drop-in replacement without requiring board redesign. Like VITA 42 connectors, the Mezalok connector is configured as a 114-position connector with contacts arranged on 0.050-inch centers in a 6 x 19 grid. A 60-position (6 x 10) connector is also available for special applications.

The new connector supports both standard XMC stacking heights 10 and 12 mm and, by customer request, a new height of 18 mm. For the carrier (daughterboard) side, the pin header is a fixed height of 4 mm. Receptacle connectors on the mezzanine side are available in heights of 6, 8, and 14 mm.

Solder balls are available either as tin-lead or RoHS-compliant SAC 405 lead-free materials.

Performance
Since the Mezalok connector is designed for high-speed applications, signal integrity analysis was performed to characterize the electrical performance of the connector. The XMC standard uses serial communications, most often with differential pairs to reduce noise. Figure 4 shows the differential impedance for the 12-mm connector pairs measured at a 50 ps rise-time using a standard VITA 42 XMC footprint. The results show a high degree of uniformity between pairs.

Conclusion: Ready to Take Flight
The design enhancements that the Mezalok connector offers for XMC applications mean that XMC is ready for prime time in military and aerospace applications. The combination of high data rates and a robust design to withstand vibration, shock, and extreme temperatures gives designers of VXS and VPX systems a high-reliability interconnection system. The connector capitalizes on existing technology that is well understood and field proven. Mini-Box contacts have been in use for decades and today support high-speed backplane and now mezzanine interconnections. Likewise, the BGA solder technology, with its compliant design, has been widely used in connectors and high-pin-count sockets with exceptional

reliability.

By Greg Powers, Market Development Manager, Global Aerospace, Defense & Marine, Tyco Electronics

Source URL (retrieved on *05/21/2013 - 6:50am*):
http://www.wirelessdesignmag.com/product-releases/2011/05/mezalok-connector-answers-need-fast-rugged-highly-reliable-solution-extreme-environments?qt-blogs=0