

LTE Ferrite Circulator Features 300W Forward Power Handling



RFMW , Ltd. announces design and sales support for a new LTE ferrite circulator featuring 300W forward power handling (2kW peak). The DiTom model D3C0780N offers a typical insertion loss of just 0.30 dB with typical isolation of 23dB from 698 – 800MHz. Ideal for LTE or “white space” testing applications, this circulator is packaged in a 1.58 x 1.62 x 0.73 inch housing, not including the passivated stainless steel, N-Type female connectors.

Details on the D3C0780N can be found here:

<http://www.rfmw.com/ProductDetail/D3C0780N-DiTom-Microwave/456884/> [1]

For more information please contact:

DiTom Microwave Stocking Distributor

RFMW, Ltd.

90 Great Oaks Blvd. #107

San Jose, Ca. 95119

PH: 408.414.1450

info@rfmw.com [2]

Posted by Janine E. Mooney, Editor

May 09, 2012

Source URL (retrieved on 01/29/2015 - 1:56pm):

http://www.wirelessdesignmag.com/product-releases/2012/05/lte-ferrite-circulator-features-300w-forward-power-handling?qt-most_popular=0&qt-digital_editions=0

LTE Ferrite Circulator Features 300W Forward Power Handling

Published on Wireless Design & Development (<http://www.wirelessdesignmag.com>)

Links:

[1] <http://www.rfmw.com/ProductDetail/D3C0780N-DiTom-Microwave/456884/>

[2] <mailto:info@rfmw.com>