Rogers' Next Gen RO4000 Materials

WDD Staff



Rogers Corporations [1] (Chandler, AZ) [NYSE:ROG [2]] next generation RO4000 materials, RO4835 high-frequency laminates, specially formulated with improved oxidation resistance were developed for applications needing a special level of electrical stability over time and temperature, while maintaining the cost advantages of a thermoset, FR-4 processable material.

Just as with RO4350B material, RO4835 laminates offer:

- A dielectric constant of 3.48 @ 10 GHz.
- A low loss tangent of 0.0037 @ 10 GHz.
- A low z-axis coefficient of thermal expansion.
- x- and y-axis expansion coefficients similar to that of copper.
- RoHS compliance.

Rogers' RT/duroid, RO3000 and RO4000 laminates feature:

- Availability in several thicknesses of 1.5, 2, and 3 mm.
- A low dielectric constant of 2.94.
- A low dissipation factor of less than 0.003 in the z axis @ 10 GHz.
- A proprietary cross-linking resin system that supports sequential bond processing.
- Controlled flow characteristics for excellent blind via fill results.

Rogers' halogen-free MCL-HE-679G/THETA laminates and prepreg products feature:

- RoHS-compliant MCL-HE-679G/THETA circuit materials.
- A relative dielectric constant of 3.90 in the z-direction @ 1 GHz.
- A low dissipation factor of 0.009 @ 1 GHz.

- A coefficient of thermal expansion of only 50 ppm/°C in the z direction.

For more information visit www.rogerscorp.com [1].

Source URL (retrieved on *03/11/2014 - 5:36am*):
http://www.wirelessdesignmag.com/product-releases/2013/02/rogers-next-gen-ro4000-materials?qt-digital_editions=0&qt-most_popular=0

Links:
[1] http://www.rogerscorp.com
[2] http://www.google.com/finance?q=NYSE%3AROG&ei=XSAmUcCFE4SxrQHmzwE